



## SPECIFICATIONS

### 10860 103' AerialCat™ Tuff Truck™ | Retail Unit

#### CHASSIS

- 96" Severe Service™ XMFD Cab with 10" Raised Roof
- Rolltek Rollover Protection System
- Driver Dash LCD Virtual Display
- Hendrickson Ultimaxx Severe Duty Rubber Suspension
- Electronic Stability Control

#### DRIVETRAIN

- Cummins ISX 12 500 HP Engine
- Allison 4000 EVS Transmission
- Meritor 22,500 LBS. Front Axle
- Meritor 58,000 LBS. Tandem Rear Axle

#### BODY

- 3/16" Aluminum 96" Wide Tuff Truck™ Body
- ROM Roll-up Doors with Painted Finish
- Hale QMAX XS 1500 gpm Single Stage Pump
- 650 Gallon UPF PolyIIE Water Tank
- ISO Ground Ladder Compliment

#### ELECTRICAL

- FRC 360° Camera System
- Class 1 Multiplex System
- HiViz FireTech and FRC LED Scene Light Package

#### AERIAL

- 103' 4 Section AerialCat™ Ladder
- 94' Horizontal Reach
- 50 mph Wind Load Rating
- 1/4" Ice on Entire Structure
- -7° to +80° Elevation Range
- 2.5 to 1 Structural Safety Factor
- 500 LBS. Dry Tip Load
- 500 LBS. Wet Tip Load Flowing 1500 GPM
- Two (2) Sets of H Style Stabilizers with 12' Stance
- Deep Penetrating Stabilizers, 11° Leveling Capability

#### DIMENSIONS

- Overall Height: 138" (11'-6")
- Overall Length: 460" (38'-4")
- Wheelbase: 227"



